

Package ‘MethEvolSIM’

April 30, 2024

Title Simulate DNA Methylation Dynamics on Different Genomic Structures along Genealogies

Version 0.1.1

Author Sara Castillo Vicente [aut, cre],
Dirk Metzler [aut, ths]

Maintainer Sara Castillo Vicente <castillo@bio.lmu.de>

Description DNA methylation is an epigenetic modification involved in genomic stability, gene regulation, development and disease.

DNA methylation occurs mainly through the addition of a methyl group to cytosines, for example to cytosines in a CpG dinucleotide context (CpG stands for a cytosine followed by a guanine).

Tissue-specific methylation patterns lead to genomic regions with different characteristic methylation levels.

E.g. in vertebrates CpG islands (regions with high CpG content) that are associated to promoter regions of expressed genes tend to be unmethylated.

‘MethEvolSIM’ is a model-based simulation software for the generation and modification of cytosine methylation patterns along a given tree, which can be a genealogy of cells within an organism, a coalescent tree of DNA sequences sampled from a population, or a species tree.

The simulations are based on an extension of the model of Grosser & Metzler (2020) <[doi:10.1186/s12859-020-3438-5](https://doi.org/10.1186/s12859-020-3438-5)> and allows for changes of the methylation states at single cytosine positions as well as simultaneous changes of methylation frequencies in genomic structures like CpG islands.

License GPL (>= 3)

Encoding UTF-8

RoxxygenNote 7.3.1

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

Config/testthat.edition 3

Imports R6

Depends R (>= 4.0)

VignetteBuilder knitr

NeedsCompilation no

Repository CRAN

Date/Publication 2024-04-30 11:30:03 UTC

R topics documented:

combiStructureGenerator	2
get_parameterValues	7
simulate_evolData	7
simulate_initialData	9
singleStructureGenerator	10
treeMultiRegionSimulator	16

Index	18
--------------	----

combiStructureGenerator
combiStructureGenerator

Description

an R6 class representing several genomic structures. Each genomic structure contained is an object of class `singleStructureGenerator`. Note that default `clone(deep=TRUE)` fails to clone `singleStructureGenerator` objects contained, use method `$copy()` instead.

Methods

Public methods:

- `combiStructureGenerator$new()`
- `combiStructureGenerator$get_singleStr()`
- `combiStructureGenerator$get_singleStr_number()`
- `combiStructureGenerator$get_island_number()`
- `combiStructureGenerator$get_island_index()`
- `combiStructureGenerator$set_IWE_events()`
- `combiStructureGenerator$get_IWE_events()`
- `combiStructureGenerator$set_name()`
- `combiStructureGenerator$get_name()`
- `combiStructureGenerator$get_own_index()`
- `combiStructureGenerator$set_own_index()`
- `combiStructureGenerator$get_parent_index()`
- `combiStructureGenerator$set_parent_index()`
- `combiStructureGenerator$get_offspring_index()`
- `combiStructureGenerator$set_offspring_index()`
- `combiStructureGenerator$add_offspring_index()`

- `combiStructureGenerator$get_mu()`
- `combiStructureGenerator$set_singleStr()`
- `combiStructureGenerator$copy()`
- `combiStructureGenerator$branch_evol()`
- `combiStructureGenerator$clone()`

Method new(): Create a new combiStructureGenerator object.

Note that this object can be generated within a treeMultiRegionSimulator object.

Usage:

```
combiStructureGenerator$new(infoStr, params = NULL, testing = FALSE)
```

Arguments:

`infoStr` A data frame containing columns 'n' for the number of sites, and 'globalState' for the favoured global methylation state. If initial equilibrium frequencies are given the dataframe must contain 3 additional columns: 'u_eqFreq', 'p_eqFreq' and 'm_eqFreq'

`params` Default NULL. When given: data frame containing model parameters.

`testing` Default FALSE. TRUE for testing output.

Returns: A new combiStructureGenerator object.

Method get_singleStr(): Public method: Get one singleStructureGenerator object in \$singleStr

Usage:

```
combiStructureGenerator$get_singleStr(i)
```

Arguments:

`i` index of the singleStructureGenerator object in \$singleStr

Returns: the singleStructureGenerator object in \$singleStr with index i

Method get_singleStr_number(): Public method: Get number of singleStructureGenerator objects in \$singleStr

Usage:

```
combiStructureGenerator$get_singleStr_number()
```

Returns: number of singleStructureGenerator object contained in \$singleStr

Method get_island_number(): Public method: Get number of singleStructureGenerator objects in \$singleStr with \$globalState "U" (CpG islands)

Usage:

```
combiStructureGenerator$get_island_number()
```

Returns: number of singleStructureGenerator in \$singleStr objects with \$globalState "U" (CpG islands)

Method get_island_index(): Public method: Get index of singleStructureGenerator objects in \$singleStr with \$globalState "U" (CpG islands)

Usage:

```
combiStructureGenerator$get_island_index()
```

Returns: index of singleStructureGenerator objects in \$singleStr with \$globalState "U" (CpG islands)

Method set_IWE_events(): Public method: Set information of the IWE events sampled in a tree branch

Usage:

```
combiStructureGenerator$set_IWE_events(a)
```

Arguments:

a value to which IWE_events should be set

Returns: NULL

Method get_IWE_events(): Public method: Get information of the IWE events sampled in a tree branch

Usage:

```
combiStructureGenerator$get_IWE_events()
```

Returns: information of the IWE events sampled in a tree branch

Method set_name(): Public method: Set the name of the leaf if evolutionary process (simulated from class treeMultiRegionSimulator) ends in a tree leaf.

Usage:

```
combiStructureGenerator$set_name(a)
```

Arguments:

a value to which name should be set

Returns: NULL

Method get_name(): Public method: Get the name of the leaf if evolutionary process (simulated from class treeMultiRegionSimulator) ended in a tree leaf.

Usage:

```
combiStructureGenerator$get_name()
```

Returns: Name of the leaf if evolutionary process (simulated from class treeMultiRegionSimulator) ended in a tree leaf. For inner tree nodes return NULL

Method get_own_index(): Public method: Set own branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$get_own_index()
```

Returns: NULL

Method set_own_index(): Public method: Get own branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$set_own_index(i)
```

Arguments:

i index of focal object

Returns: Own branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Method `get_parent_index()`: Public method: Get parent branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$get_parent_index()
```

Returns: Parent branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Method `set_parent_index()`: Public method: Set parent branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$set_parent_index(i)
```

Arguments:

i set parent_index to this value

Returns: NULL

Method `get_offspring_index()`: Public method: Get offspring branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$get_offspring_index()
```

Returns: Offspring branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Method `set_offspring_index()`: Public method: Set offspring branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$set_offspring_index(i)
```

Arguments:

i set offspring_index to this value

Returns: NULL

Method `add_offspring_index()`: Public method: Add offspring branch index in the tree along which the evolutionary process is simulated (from class treeMultiRegionSimulator).

Usage:

```
combiStructureGenerator$add_offspring_index(i)
```

Arguments:

i index to be added

Returns: NULL

Method `get_mu()`: Public method.

Usage:

```
combiStructureGenerator$get_mu()
```

Returns: Model parameter for the rate of the IWE evolutionary process (per island and branch length).

Method `set_singleStr()`: Public method: Clone each singleStructureGenerator object in \$singleStr

Usage:

```
combiStructureGenerator$set_singleStr(singStrList)
```

Arguments:

`singStrList` object to be cloned

Returns: NULL

Method `copy()`: Public method: Clone combiStructureGenerator object and all singleStructureGenerator objects in it

Usage:

```
combiStructureGenerator$copy()
```

Returns: cloned combiStructureGenerator object

Method `branch_evol()`: Simulate CpG dinucleotide methylation state evolution along a tree branch. The function samples the IWE events on the tree branch and simulates the evolution through the SSE and IWE processes.

Usage:

```
combiStructureGenerator$branch_evol(branch_length, dt, testing = FALSE)
```

Arguments:

`branch_length` Length of the branch.

`dt` Length of SSE time steps.

`testing` Default FALSE. TRUE for testing purposes.

Details: It handles both cases where IWE events are sampled or not sampled within the branch.

Returns: Default NULL. If testing = TRUE it returns information for testing purposes.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
combiStructureGenerator$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

```
get_parameterValues      Get Default Parameter Values
```

Description

This function retrieves parameter values for the DNA methylation simulation.

Usage

```
get_parameterValues(rootData = NULL)
```

Arguments

rootData NULL to return default parameter values. For data parameter values, provide rootData as the output of simulate_initialData()\$data.

Details

The function called without arguments returns default parameter values. When rootData (as \$data output of simulate_initialData()) is given, it returns data parameter values.

Value

A data frame containing default parameter values.

Examples

```
# Get default parameter values
default_values <- get_parameterValues()

# Get parameter values of simulate_initialData() output
custom_params <- get_parameterValues()
infoStr <- data.frame(n = c(5, 10), globalState = c("M", "U"))
rootData <- simulate_initialData(infoStr = infoStr, params = custom_params)$data
rootData_paramValues <- get_parameterValues(rootData = rootData)
```

```
simulate_evolData      Simulate Data Evolution along a Tree
```

Description

This function simulates methylation data evolution along a tree. Either by simulating data at the root of the provided evolutionary tree (if infoStr is given) or by using pre-existing data at the root (if rootData is given) and letting it evolve along the tree.

Usage

```
simulate_evolData(
  infoStr = NULL,
  rootData = NULL,
  tree,
  params = NULL,
  dt = 0.01,
  n_rep = 1,
  only_tip = TRUE
)
```

Arguments

infoStr	A data frame containing columns 'n' for the number of sites, and 'globalState' for the favoured global methylation state. If customized initial equilibrium frequencies are given, it also contains columns 'u_eqFreq', 'p_eqFreq', and 'm_eqFreq' with the equilibrium frequency values for unmethylated, partially methylated, and methylated.
rootData	The output of the simulate_initialData()\$data function. It represents the initial data at the root of the evolutionary tree.
tree	A string in Newick format representing the evolutionary tree.
params	Optional data frame with specific parameter values. Structure as in get_parameterValues() output. If not provided, default values will be used.
dt	Length of time step for Gillespie's Tau-Leap Approximation (default is 0.01).
n_rep	Number of replicates to simulate (default is 1).
only_tip	Logical indicating whether to extract data only for tips (default is TRUE, FALSE to extract the information for all the tree branches).

Value

A list containing the parameters used (\$params), the length of the time step used for the Gillespie's tau-leap approximation (\$dt, default 0.01), the tree used (\$tree). simulated data and the simulated data (\$data). In \$data, each list element corresponds to a simulation replicate.

- If only_tip is TRUE: In \$data, each list element corresponds to a simulation replicate. Each replicate includes one list per tree tip, each containing:
 - The name of each tip in the simulated tree (e.g. replicate 2, tip 1: \$data[[2]][[1]]\$name).
 - A list with the sequence of methylation states for each tip-specific structure (e.g. replicate 1, tip 2, 3rd structure: \$data[[1]][[2]]\$seq[[3]]). The methylation states are encoded as 0 for unmethylated, 0.5 for partially methylated, and 1 for methylated.
- If only_tip is FALSE, \$data contains 2 lists:
 - \$data\$branchInTree: a list in which each element contains the information of the relationship with other branches:
 - * Index of the parent branch (e.g. branch 2): \$data\$branchInTree[[2]]\$parent_index
 - * Index(es) of the offspring branch(es) (e.g. branch 1 (root)): \$data\$branchInTree[[1]]\$offspring_index

- `$data$sim_data`: A list containing simulated data. Each list element corresponds to a simulation replicate. Each replicate includes one list per tree branch, each containing:
 - * The name of each branch in the simulated tree. It's NULL for the tree root and inner nodes, and the name of the tips for the tree tips. (e.g. replicate 2, branch 1: `$data$sim_data[[2]][[1]]$name`)
 - * Information of IWE events on that branch. It's NULL for the tree root and FALSE for the branches in which no IWE event was sampled, and a list containing `$islands` with the index(es) of the island structure(s) that went through the IWE event and `$times` for the branch time point(s) in which the IWE was sampled. (e.g. replicate 1, branch 3: `$data$sim_data[[1]][[3]]$IWE`)
 - * A list with the sequence of methylation states for each structure (the index of the list corresponds to the index of the structures). The methylation states are encoded as 0 for unmethylated, 0.5 for partially methylated, and 1 for methylated. (e.g. replicate 3, branch 2, structure 1: `$data$sim_data[[3]][[2]]$seq[[1]]`)
 - * A list with the methylation equilibrium frequencies for each structure (the index of the list corresponds to the index of the structures). Each structure has a vector with 3 values, the first one corresponding to the frequency of unmethylated, the second one to the frequency of partially methylated, and the third one to the frequency of methylated CpGs. (e.g. replicate 3, branch 2, structure 1: `$data$sim_data[[3]][[2]]$eqFreqs[[1]]`)

Examples

```
# Example data
infoStr <- data.frame(n = c(10, 100, 10), globalState = c("M", "U", "M"))

# Simulate data evolution along a tree with default parameters
simulate_evolData(infoStr = infoStr, tree = "(A:0.1,B:0.1);")

# Simulate data evolution along a tree with custom parameters
custom_params <- get_parameterValues()
custom_params$iota <- 0.5
simulate_evolData(infoStr = infoStr, tree = "(A:0.1,B:0.1);", params = custom_params)
```

`simulate_initialData` *Simulate Initial Data*

Description

This function simulates initial data based on the provided information and parameters.

Usage

```
simulate_initialData(infoStr, params = NULL)
```

Arguments

<code>infoStr</code>	A data frame containing columns 'n' for the number of sites, and 'globalState' for the favoured global methylation state. If customized equilibrium frequencies are given, it also contains columns 'u_eqFreq', 'p_eqFreq' and 'm_eqFreq' with the equilibrium frequency values for unmethylated, partially methylated and methylated.
<code>params</code>	Optional data frame with specific parameter values. Structure as in <code>get_parameterValues()</code> output. If not provided, default values will be used.

Details

The function performs several checks on the input data and parameters to ensure they meet the required criteria and simulates DNA methylation data.

Value

A list containing the simulated data (\$data) and parameters (\$params).

Examples

```
# Example data
infoStr <- data.frame(n = c(10, 100, 10), globalState = c("M", "U", "M"))

# Simulate initial data with default parameters
simulate_initialData(infoStr = infoStr)

# Simulate data evolution along a tree with custom parameters
custom_params <- get_parameterValues()
custom_params$iota <- 0.5
simulate_initialData(infoStr = infoStr, params = custom_params)
```

singleStructureGenerator
singleStructureGenerator

Description

an R6 class representing a single genomic structure

Methods

Public methods:

- `singleStructureGenerator$init_neighbSt()`
- `singleStructureGenerator$initialize_ratetree()`
- `singleStructureGenerator$new()`
- `singleStructureGenerator$get_seq()`

- `singleStructureGenerator$get_seqFirstPos()`
- `singleStructureGenerator$get_seq2ndPos()`
- `singleStructureGenerator$get_seqLastPos()`
- `singleStructureGenerator$get_seq2ndButLastPos()`
- `singleStructureGenerator$get_combiStructure_index()`
- `singleStructureGenerator$update_interStr_firstNeighbSt()`
- `singleStructureGenerator$update_interStr_lastNeighbSt()`
- `singleStructureGenerator$get_eqFreqs()`
- `singleStructureGenerator$SSE_evol()`
- `singleStructureGenerator$IWE_evol()`
- `singleStructureGenerator$get_alpha_pI()`
- `singleStructureGenerator$get_beta_pI()`
- `singleStructureGenerator$get_alpha_mI()`
- `singleStructureGenerator$get_beta_mI()`
- `singleStructureGenerator$get_alpha_pNI()`
- `singleStructureGenerator$get_beta_pNI()`
- `singleStructureGenerator$get_alpha_mNI()`
- `singleStructureGenerator$get_beta_mNI()`
- `singleStructureGenerator$get_alpha_Ri()`
- `singleStructureGenerator$get_iota()`
- `singleStructureGenerator$get_Ri_values()`
- `singleStructureGenerator$clone()`

Method `init_neighbSt():` Public method: Initialization of \$neighbSt

This function initiates each CpG position \$neighbSt as encoded in \$mapNeighbSt_matrix Positions at the edge of the entire simulated sequence use their only neighbor as both neighbors.

Usage:

```
singleStructureGenerator$init_neighbSt()
```

Returns: NULL

Method `initialize_ratetree():` Public method: Initialization of \$ratetree

This function initializes \$ratetree

Usage:

```
singleStructureGenerator$initialize_ratetree()
```

Returns: NULL

Method `new():` Create a new singleStructureGenerator object.

Note that this object is typically generated within a combiStructureGenerator object.

Usage:

```
singleStructureGenerator$new(
  globalState,
  n,
  eqFreqs = NULL,
```

```

    combiStr = NULL,
    combiStr_index = NULL,
    params = NULL,
    testing = FALSE
)

```

Arguments:

globalState Character. Structure's favored global state: "M" for methylated (island structures) / "U" for unmethylated (non-island structures).

n Numerical Value. Number of CpG positions

eqFreqs Default NULL. When given: numerical vector with structure's methylation state equilibrium frequencies (for unmethylated, partially methylated and methylated)

combiStr Default NULL. When initiated from combiStructureGenerator: object of class combiStructureGenerator containing it

combiStr_index Default NULL. When initiated from combiStructureGenerator: index in Object of class combiStructureGenerator

params Default NULL. When given: data frame containing model parameters

testing Default FALSE. TRUE for testing output

Returns: A new *singleStructureGenerator* object.

Method get_seq(): Public method: Get object's methylation state sequence

Encoded with 1 for unmethylated, 2 for partially methylated and 3 for methylated

Usage:

singleStructureGenerator\$get_seq()

Returns: vector with equilibrium frequencies of unmethylated, partially methylated and methylated

Method get_seqFirstPos(): Public method: Get first sequence position methylation state

Usage:

singleStructureGenerator\$get_seqFirstPos()

Returns: numerical encoding of first position's methylation state

Method get_seq2ndPos(): Public method: Get second sequence position methylation state

Usage:

singleStructureGenerator\$get_seq2ndPos()

Returns: numerical encoding of second position's methylation state. NULL if position does not exist

Method get_seqLastPos(): Public method: Get first sequence position methylation state

Usage:

singleStructureGenerator\$get_seqLastPos()

Returns: numerical encoding of first position's methylation state

Method get_seq2ndButLastPos(): Public method: Get second but last sequence position methylation state

Usage:

```
singleStructureGenerator$get_seq2ndButLastPos()
```

Returns: numerical encoding of second but last position's methylation state. NULL if position does not exist

Method `get_combiStructure_index()`: Public method: Get index in object of class combiStructureGenerator

Usage:

```
singleStructureGenerator$get_combiStructure_index()
```

Returns: index in object of class combiStructureGenerator

Method `update_interStr_firstNeighbSt()`: Public method: Update neighbSt of next singleStructureGenerator object within combiStructureGenerator object

This function is used when the last \$seq position of a singleStructureGenerator object changes methylation state to update the neighbSt position

Usage:

```
singleStructureGenerator$update_interStr_firstNeighbSt(  
  leftNeighbSt,  
  rightNeighbSt  
)
```

Arguments:

`leftNeighbSt` \$seq state of left neighbor (left neighbor is in previous singleStructureGenerator object)

`rightNeighbSt` \$seq state of right neighbor

Returns: NULL

Method `update_interStr_lastNeighbSt()`: Public method: Update neighbSt of previous singleStructureGenerator object within combiStructureGenerator object

Usage:

```
singleStructureGenerator$update_interStr_lastNeighbSt(  
  leftNeighbSt,  
  rightNeighbSt  
)
```

Arguments:

`leftNeighbSt` \$seq state of right neighbor (left neighbor is in next singleStructureGenerator object)

`rightNeighbSt` \$seq state of right neighbor

Returns: NULL

Method `get_eqFreqs()`: Public method: Get object's equilibrium Frequencies

Usage:

```
singleStructureGenerator$get_eqFreqs()
```

Returns: vector with equilibrium frequencies of unmethylated, partially methylated and methylated

Method SSE_evol(): Public method. Simulate how CpG dinucleotide methylation state changes due to the SSE process along a time step of length dt

Usage:

```
singleStructureGenerator$SSE_evol(dt, testing = FALSE)
```

Arguments:

dt time step length.

testing logical value for testing purposes. Default FALSE.

Returns: default NULL. If testing TRUE it returns a list with the number of events sampled and a dataframe with the position(s) affected, new state and old methylation state.

Method IWE_evol(): Public Method. Simulate IWE Events

Simulates how CpG Islands' methylation state frequencies change and simultaneous sites change methylation state along a branch of length t according to the SSE-IWE model.

Usage:

```
singleStructureGenerator$IWE_evol(testing = FALSE)
```

Arguments:

testing logical value for testing purposes. Default FALSE.

Details: The function checks if the methylation equilibrium frequencies (eqFreqs) and sequence observed frequencies (obsFreqs) change after the IWE event. If there is a change in either frequencies, the corresponding change flags(eqFreqsChange in the infoIWE list will be set to TRUE.

Returns: If testing = TRUE it returns a list. If there was a change in the equilibrium frequencies the list contains the following 7 elements, if not it contains the first 3 elements:

eqFreqsChange logical indicating if there was a change in the equilibrium frequencies.

old_eqFreqs Original equilibrium frequencies before the IWE event.

new_eqFreqs New equilibrium frequencies after the IWE event.

old_obsFreqs Original observed frequencies before the IWE event.

new_obsFreqs New observed frequencies after the IWE event.

IWE_case Description of the IWE event case.

Mk Transition matrix used for the IWE event.

Method get_alpha_pI(): Public Method.

Usage:

```
singleStructureGenerator$get_alpha_pI()
```

Returns: Model parameter alpha_pI for sampling island equilibrium frequencies

Method get_beta_pI(): Public Method.

Usage:

```
singleStructureGenerator$get_beta_pI()
```

Returns: Model parameter for sampling island equilibrium frequencies

Method get_alpha_mI(): Public Method.

Usage:

```
singleStructureGenerator$get_alpha_mI()
```

Returns: Model parameter for sampling island equilibrium frequencies

Method get_beta_mI(): Public Method.

Usage:

```
singleStructureGenerator$get_beta_mI()
```

Returns: Model parameter for sampling island equilibrium frequencies

Method get_alpha_pNI(): Public Method.

Usage:

```
singleStructureGenerator$get_alpha_pNI()
```

Returns: Model parameter for sampling non-island equilibrium frequencies

Method get_beta_pNI(): Public Method.

Usage:

```
singleStructureGenerator$get_beta_pNI()
```

Returns: Model parameter for sampling non-island equilibrium frequencies

Method get_alpha_mNI(): Public Method.

Usage:

```
singleStructureGenerator$get_alpha_mNI()
```

Returns: Model parameter for sampling non-island equilibrium frequencies

Method get_beta_mNI(): Public Method.

Usage:

```
singleStructureGenerator$get_beta_mNI()
```

Returns: Model parameter for sampling non-island equilibrium frequencies

Method get_alpha_Ri(): Public Method.

Usage:

```
singleStructureGenerator$get_alpha_Ri()
```

Returns: Model parameter for gamma distribution shape to initialize the 3 \$Ri_values

Method get_iota(): Public Method.

Usage:

```
singleStructureGenerator$get_iota()
```

Returns: Model parameter for gamma distribution expected value to initialize the 3 \$Ri_values

Method get_Ri_values(): Public Method.

Usage:

```
singleStructureGenerator$get_Ri_values()
```

Returns: The 3 \$Ri_values

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
singleStructureGenerator$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

treeMultiRegionSimulator

treeMultiRegionSimulator

Description

an R6 class representing the methylation state of GpGs in different genomic structures in the nodes of a tree.

The whole CpG sequence is an object of class `combiStructureGenerator`. Each genomic structure in it is contained in an object of class `singleStructureGenerator`.

Public fields

`Branch` Public attribute: List containing objects of class `combiStructureGenerator`

`branchLength` Public attribute: Vector with the corresponding branch lengths of each `$Branch` element

Methods

Public methods:

- [`treeMultiRegionSimulator\$treeEvol\(\)`](#)
- [`treeMultiRegionSimulator\$new\(\)`](#)
- [`treeMultiRegionSimulator\$clone\(\)`](#)

Method `treeEvol()`: Simulate CpG dinucleotide methylation state evolution along a tree. The function splits a given tree and simulates evolution along its branches. It recursively simulates evolution in all of the subtrees in the given tree until the tree leafs

Usage:

```
treeMultiRegionSimulator$treeEvol(
  Tree,
  dt = 0.01,
  parent_index = 1,
  testing = FALSE
)
```

Arguments:

`Tree` String. Tree in Newick format. When called recursively it is given the corresponding subtree.

`dt` Length of SSE time steps.

`parent_index` Default 1. When called recursively it is given the corresponding parent branch index.

`testing` Default FALSE. TRUE for testing purposes.

`Returns:` NULL

Method new(): Create a new treeMultiRegionSimulator object. \$Branch is a list for the tree branches, its first element represents the tree root.

Note that one of either infoStr or rootData needs to be given. Not both, not neither.

Usage:

```
treeMultiRegionSimulator$new(
  infoStr = NULL,
  rootData = NULL,
  tree,
  params = NULL,
  dt = 0.01,
  testing = FALSE
)
```

Arguments:

`infoStr` A data frame containing columns 'n' for the number of sites, and 'globalState' for the favoured global methylation state. If initial equilibrium frequencies are given the dataframe must contain 3 additional columns: 'u_eqFreq', 'p_eqFreq' and 'm_eqFreq'

`rootData` combiStructureGenerator object. When given, the simulation uses its parameter values.

`tree` tree

`params` Default NULL. When given: data frame containing model parameters. Note that root-Data is given, its parameter values are used.

`dt` length of the dt time steps for the SSE evolutionary process

`testing` Default FALSE. TRUE for testing output.

`Returns:` A new treeMultiRegionSimulator object.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
treeMultiRegionSimulator$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Index

combiStructureGenerator, 2
get_parameterValues, 7
simulate_evolData, 7
simulate_initialData, 9
singleStructureGenerator, 10
treeMultiRegionSimulator, 16