

Package ‘SearchTrees’

October 12, 2022

Type Package

Title Spatial Search Trees

Version 0.5.5

Date 2022-10-03

Author Gabriel Becker

Maintainer Gabriel Becker <gabembecker@gmail.com>

Description The QuadTree data structure is useful for fast, neighborhood-restricted lookups. We use it to implement fast k-Nearest Neighbor and Rectangular range lookups in 2 dimenions. The primary target is high performance interactive graphics.

Depends methods

License LGPL

LazyLoad yes

URL <https://github.com/gmbecker/SearchTrees>

BugReports <https://github.com/gmbecker/SearchTrees/issues>

NeedsCompilation yes

Repository CRAN

Date/Publication 2022-10-03 22:20:06 UTC

R topics documented:

createTree	2
knnLookup	3
knnLookup-methods	4
QuadTree-class	5
rectLookup	6
rectLookup-methods	7
SearchTree-class	7

Index	9
--------------	----------

 createTree

 Create a Search Tree Index

Description

Create a search tree from the supplied data for use in during future lookups.

Usage

```
createTree(data, treeType = "quad", dataType = "point",
           columns = if (dataType=="point") 1:2 else 1:4, ...)
```

Arguments

data	data.frame or matrix. Data to be indexed.
treeType	Character. Indicates type of index tree to be created. Currently only "quad" (quad trees) is supported.
dataType	Character. Indicates type of data being indexed. Currently "point", and "rect" are supported corresponding to points and rectangles, respectively. Defaults to "point".
columns	Numeric. Indicates columns in data the information to be indexed can be found. Length depends on value of dataType (2 for "point" and 4 for "rect"). Defaults to columns 1 and 2. See Details.
...	Any additional/type specific parameters to be passed to the tree creation function. These include: maxDepth: Numeric. Maximum depth of the tree. Defaults to 7. minNodeArea: Numeric. Minimum (rectangular) area to be represented by a single node. When set, this overrides maxDepth

Details

For a point based tree, the two columns specified in columns represent the x and y values of the points.

For a rectangle based tree, four columns must be specified. These columns represent the x and y coordinates of point 1 and the x and y coordinates of point 2, in that order (where point 1 and point 2 specify the rectangle to be stored).

Value

The class of the returned object depends on the tree type created, though all will inherit from the SearchTree S4 class and have the following slots:

ref	An external pointer to the C level data structure.
numNodes	Total number of nodes comprising the tree.
dataNodes	Number of nodes which store at least one data point.

maxDepth	Maximum depth of the tree.
maxBucket	Maximum number of data points stored in a single node.
totalData	Number of items indexed in the tree.
dataType	Type of objects stored in the tree.

Author(s)

Gabriel Becker

References

Finkel, R. A. and Bentley, J. L. "Quad Trees, a Data Structure for Retrieval on Composite Keys." Acta Informatica 4, 1-9, 1974.

See Also

[SearchTree](#) linkS4Class{QuadTree}

Examples

```
x = rnorm(100)
y = rnorm(100)
dat = cbind(x,y)
tree = createTree(dat)
```

knnLookup

Perform k-Nearest Neighbors Lookup Using a Search Tree

Description

This function performs fast k-Nearest Neighbors lookup on a SearchTree object

Usage

```
knnLookup(tree, newx, newy, newdat, columns = 1:2, k = 5)
```

Arguments

tree	An object which inherits from the SearchTree S4 class.
newx	Numeric. Vector of x values for the points to look up neighbors for.
newy	Numeric. Vector of y values for the points to look up neighbors for.
newdat	Matrix or data.frame. Data containing x and y values of the points to look up neighbors for. Ignored if x and y are specified.
columns	Numeric. Columns x and y values can be found in within newdat.
k	Numeric. Number of neighbors to find for each point.

Value

The return value is an integer matrix indicating the indices in the original data used to create `treeE` where the nearest neighbors were found. Row indicates the indice of the new point, while column indicates the order of the `k` neighbors.

Note

No defined order is specified for exact ties in distance.

Author(s)

Gabriel Becker

See Also

[createTree](#) [rectLookup](#)

Examples

```
x = rnorm(100)
y = rnorm(100)
tree = createTree(cbind(x,y))
newx = c(0, .5)
newy = c(.5, 0)
inds = knnLookup(tree, newx, newy, k=7)

ch = rep(1, times=100)
ch[inds[1:7]] = 3
ch[inds[8:14]] = 5
cls = rep("black", times=100)
cls[inds[1:7]] = "red"
cls[inds[8:14]] = "blue"

plot(x,y, pch=ch, col = cls)
abline(v=newx[1], h = newy[1], col="red")
abline(v=newx[2], h = newy[2], col = "blue")
```

knnLookup-methods

~~ *Methods for Function knnLookup in Package SearchTrees* ~~

Description

~~ *Methods for function knnLookup in package SearchTrees* ~~

Methods

`signature(tree = "QuadTree")`

QuadTree-class	Class "QuadTree"
----------------	------------------

Description

A class representing a Quad Tree object for storing 2 dimensional points for efficient rectangular range and knn lookup.

Objects from the Class

Objects can be created by calls of the form `new("QuadTree", ...)`.

Slots

ref: Object of class "externalptr" Pointer to the internal representation of the tree

numNodes: Object of class "integer" Number of nodes in the tree

dataNodes: Object of class "integer" Number of nodes in the tree which are storing data

maxDepth: Object of class "integer" Maximum depth of the tree.

maxBucket: Object of class "integer" Maximum number of data points which are stored at a single node

totalData: Object of class "integer" Number of objects stored in the tree

dataType: Object of class "character" Indicates type of data stored in the tree.

Extends

Class "[SearchTree](#)", directly.

Methods

knnLookup signature(`tree = "QuadTree"`): ...

rectLookup signature(`tree = "QuadTree"`): ...

Note

When using `createIndex` to create a `quadTree`, only two columns of the matrix/data.frame passed to the function will be used to create the tree. See the columns argument in [createTree](#)

Author(s)

Gabriel Becker

See Also

[createTree](#)

Examples

```
showClass("QuadTree")
```

`rectLookup`*Perform Rectangular Lookup in 2d Space*

Description

Determine which objects, stored in a SearchTrees indexing object, fall within a given rectangle in two-dimensional space.

Usage

```
rectLookup(tree, ptOne, ptTwo, xlims, ylims)
```

Arguments

<code>tree</code>	SearchTree. A SearchTree object to perform the lookup on.
<code>ptOne</code>	Numeric. A numeric of length two indicating x and y values for one corner of the rectangle.
<code>ptTwo</code>	Numeric. A numeric of length two indicating x and y values for the corner of the rectangle opposite to ptOne
<code>xlims</code>	Numeric. A numeric vector indicating the minimum and maximum x value for the rectangle. Overrides ptOne and ptTwo
<code>ylims</code>	Numeric. A numeric vector indicating the minimum and maximum y value for the rectangle. Overrides ptOne and ptTwo

Details

In the case of lookup for rectangular objects, any rectangle which overlaps the query rectangle will be returned.

Value

A numeric vector indicating the indices of the object (in the order they were in when the SearchTree object was created) which fall (at least partially) within the rectangular query.

Author(s)

Gabriel Becker

See Also

[QuadTree knnLookup](#)

Examples

```
x = rnorm(100)
y = rnorm(100)
x2 = x + runif(100, .5, 2)
y2 = y + runif(100, .5, 2)
dat2 = cbind(x, y, x2, y2)
tree2 = createTree(dat2, dataType="rect", columns= 1:4)
inrect = rectLookup(tree2, xlim = c(0,1), ylim=c(0, 1))
col = rgb(0, 1, 0, alpha=.5)
plot(x, y2, col="white")
rect(x[inrect], y[inrect], x2[inrect], y2[inrect], col=col)
rect(0, 0, 1, 1, col="blue", lwd=3)
```

rectLookup-methods *Methods for Function rectLookup in Package SearchTrees*

Description

Methods for function rectLookup in package **SearchTrees**

Methods

signature(tree = "QuadTree")

SearchTree-class *Class "SearchTree"*

Description

A virtual class representing a search tree for storing geometric points in a manner designed for efficient lookup.

Objects from the Class

This is a virtual class so objects of class SearchTree cannot be created directly.No methods defined with class "SearchTree" in the signature.

Slots

ref: Object of class "externalptr" Pointer to the internal representation of the tree.
numNodes: Object of class "integer" Number of nodes in the tree
dataNodes: Object of class "integer" Number of nodes in the tree which are storing data.
maxDepth: Object of class "integer" Maximum depth of the tree
maxBucket: Object of class "integer" Maximum number of data points stored in a single node
totalData: Object of class "integer" Number of data objects stored in the tree.
dataType: Object of class "character" Indicates type of data stored in the tree.

Methods

knnLookup, rectLookup

Author(s)

Gabriel Becker

See Also

[QuadTree createTree](#)

Index

- * **classes**
 - QuadTree-class, 5
 - SearchTree-class, 7
 - * **indexing**
 - createTree, 2
 - * **knn**
 - knnLookup, 3
 - * **lookup**
 - knnLookup, 3
 - rectLookup, 6
 - SearchTree-class, 7
 - * **methods**
 - knnLookup-methods, 4
 - rectLookup-methods, 7
 - * **neighbors**
 - knnLookup, 3
 - * **quadtree**
 - createTree, 2
 - * **query**
 - rectLookup, 6
 - * **rectangular**
 - rectLookup, 6
- createTree, 2, 4, 5, 8
- knnLookup, 3, 6
- knnLookup, QuadTree-method (knnLookup), 3
- knnLookup, QuadTree-method (knnLookup-methods), 4
- knnLookup-methods, 4
- QuadTree, 6, 8
- QuadTree-class, 5
- rectLookup, 4, 6
- rectLookup, QuadTree-method (rectLookup), 6
- rectLookup, QuadTree-method (rectLookup-methods), 7
- rectLookup-methods, 7
- SearchTree, 3, 5
- SearchTree-class, 7