NAME

edgepaint – edge coloring to disambiguate crossing edges

SYNOPSIS

[*options*] [**−o** *outfile*] [*files*]

DESCRIPTION

edgepaint takes as input a graph in DOT format with node position information (the *pos* attribute) and colors the edges in a manner making it easier to tell them apart.

OPTIONS

The following options are supported:

−−accuracy=*e*
: Accuracy with which to find the maximally different coloring for each node with regard to its neighbors. Default *e* = 0.01.

−−angle=*a*
: Color two edges differently if their incidence angle is less than *a* degrees. Default *a* = 15.

−−random_seed=*s*
: Random seed to use. *s* must be an integer. If *s* is negative, we do |*s*| iterations with different seeds and pick the best.

−−lightness=*l1,l2*
: Only applies for the "lab" color scheme: *l1* and *l2* must integers, with 0 <= *l1* <= *l2* <=100. By default, we use "0,70".

−−share_endpoint
: If this option is specified, edges that share a node are not considered in conflict if they are close to parallel but are on the opposite sides of the node (around 180 degree).

−o *f*
: Write output to file *f* (default: stdout).

−−color_scheme=*c*
: Specifies the color scheme. This can be "rgb", "gray", "lab" (default); or a comma-separated list of RGB colors in hex (e.g., "#ff0000,#aabbed,#eeffaa") representing a palette; or a string specifying a Brewer color scheme (e.g., "accent7"; see https://graphviz.org/doc/info/colors.html#brewer).

−v
: Turns on verbose mode.

−?
: Print usage and exit.

BUGS

At present, **edgepaint** does not handle graphs with loops or directed multiedges. So, a graph with edges *a* −> *b* and *b* −> *a* is acceptable, but not if it has edges *a* −> *b* and *a* −> *b* or *a* −− *b* and *a* −− *b*. Ports are ignored in this analysis, so having *a.x* −> *b* and *a.y* −> *b* is also not supported.

AUTHOR

Yifan Hu <yifanhu@yahoo.com>

SEE ALSO

gvmap(1), sfdp(1), neato (1), dot(1)